

AMENDED CLAIM LISTING

Please amend the Application as follows (This listing of the claims will replace all prior versions, and listings, of claims in the application.):

1. (cancelled)
2. (cancelled)
3. (cancelled)
4. (currently amended) Equipment for a change of rotary gobos comprising a carrier disc provided with circular apertures allowing for lighting of gobos and furnished with a flexible holder to removably secure[support] interchangeable segments with the gobos to the carrier disc, wherein each segment is provided with a lamella to be held by [for attachment in] the holder and with a setting portion to fix the position of the segment on the carrier disc, wherein each segment is provide with a bearing supporting a driver with a gobo, wherein a bearing inside ring is provided by a driver outer rim, and a bearing outside ring is attached to the segment lamella by a dismountable-connection, while the driver comprises a flange with a spur toothing.
5. (currently amended) Equipment for a change of rotary gobos comprising a carrier disc provided with circular apertures allowing for lighting of gobos and furnished with a flexible holder to removably secure[support] interchangeable segments with the gobos to the carrier disc, wherein each segment is provided with a lamella to be received and held by [for attachment in]the holder and with a setting portion to position the segment on the carrier disc, wherein the setting portion for positioning the segment on the carrier disc comprises a dismountable-connection for attachment of the gobo bearing outer ring on the lamella.
6. (previously presented) Equipment for a change of rotary gobos according to claim 4 or claim 5, wherein the holder comprises a system of flexible fingers in a fan shaped arrangement, the fingers being at inside ends fixed to the carrier disc, and on the outside free ends is adapted to allow for

RESPONSE

Page 4

Atty. Docket No.: ROBE001US0

Customer ID No.: 58417

Appl. No.: US10/534,927

insertion of the segment lamellas between the fingers and the carrier disc.

7. (previously presented). Equipment for a change of rotary gobos according to claim 6, wherein inside ends of the fingers are integrated into one unit, while the number of fingers within this unit corresponds to the number of segments to be supported by the carrier disc.